

Flex System CyberKey Vault II WR Module

Part Number: FS-CV02

CAW	Version 8.0	Version 9.4 or newer
Enterprise	✓*	✓
Basic	✓*	✓

The CyberKey Vault WR Module II is a secure, ruggedized, outdoor vault that stores an unprogrammed CyberKey. When approved credentials are presented, the CyberKey is programmed and can be removed from the Vault. Required items: Flex System Controller, credential input module(s), and CyberKey(s).

* CyberAudit-Web 9.4 and a Flex II System are required for the use of Gen 2 keys.
Vault is backwards compatible with Flex I systems.



Specifications

Physical	Clear anodized aluminum
Operating Temperature	-40° to 140° F (-40° to 60° C)
Weight	21.9 oz (622 g)
Dimensions	4.80" L x 3.125" D (121.9 mm x 79.4 mm)
Visual Output	Blue LED
Power	Via RS485, CAT 5 patch cable from a Flex System Controller
Connection	RJ45
Humidity	0 to 100%
Compatible Keys	All Gen 1 and Gen 2 CyberKeys*
Mounting Hole	2.65" D (67.3 mm)
Controller Distance	100 feet using CAT 5 Ethernet patch cable

Notes:
Dimensions in inches (mm)
Drawing not to scale
Ø indicates diameter

